



Mold Oil Wood / Steel and Plywood

Product Description

It is a water-based / oil-based / mold release oil that prevents the adhesions between fresh concrete and formwork, allowing the mold to be separated from the concrete more easily and to obtain concrete with a smooth surface.

Areas of Use

- Absorbent mold surfaces, especially wooden molds.
- Steel, plastic, ply-wood molds,
- Applications to increase mold efficiency,
- Situations in which mold workmanship is desired to be accelerated.

Advantages

- Its application is easy.
- It allows the mold to be separated from the concrete clean and easily.
- It provides smoother and good-looking concrete surfaces.
- It decreases the dirt on the concrete surfaces and does not spoil the appearance.
- It reduces mold cost and workmanship.



Application Requirements

The ambient temperature should be between +5 °C and +35 °C.

Application Tools

Brush, roller

Warnings & Suggestions

- After application, all tools used should be washed with water before drying.
- Foreign materials must not be added.
- The amount of consumption indicated is a general knowledge.
- It can vary depending on application conditions and surface characteristics.

Teknik Bilgi

Technical Information is relative to 55% (± 5 °C) relative humidity environment at 23 °C (± 2 °C).

Aspect	Liquid
Density	0.86 \pm 0.02 kg/l (at 20°C)
Viscosity	29-36 cp
Freezing Point	< -10°C (without adding water)

