

Pool Primer Pool Insulation Paint Primer

Product Description

It is an acrylic based, surface adhesive primer prepared for Pool Paint.

Areas of Us

- On concrete, plaster and screed,
- In pools, water tanks, water reservoirs, metal tanks and water cisterns,
- Ornamental pools, ponds, dams, water channels,
- In treatment and balance tanks.

Advantages

- It is not affected by water and water pressure
- It is elastic, It does not crack, It does not swell, peel.
- It is not affected by UV rays and pool chemicals.
- It is extremely resistant to alkali and chlorine.
- Its color does not fade with time, it does not deteriorate underwater, it does not erode.
- It can be easily applied by anyone.

Application Instruction

- The surface should be clean, dry and free from foreign substances such as dirt, oil, coating, surface curing materials.
- Surface repairs, filling of gaps/holes must be done with Newkim Repair Mortar.
- Concrete and plaster coated surfaces must be primed with Newkim Pool Point Primer before application.
- It should be applied with a brush or roller and left to dry.



Product Preparation (Mix)

It is ready for use.

Specifications

- Volumetric Solids %: 60 ± 2%
- Density :1.15 1.30 gr/ml

Application Requirements

- The ambient temperature should be between +5 °C and +35 °C.
- It should not be applied on surfaces that are frozen, melting or in danger of rain or frost within 24 hours.

Application Tools

Rol

Warnings & Suggestions

- Never dilute with water or other chemicals.
- Avoid application under strong wind or sun.
- It should not be applied on surfaces that are frozen, melting or that are in danger of frost within 24 hours.
- The surface temperature to be applied must be between +5 °C and +35 °C.







