



S-705 Impregnation Transparent Waterproofing

Product Description

Transparent, solvent based waterproofing which gives water repellent properties to the surface where it is used.

Areas of Use

- It prevents water leakages by strengthening the areas where horizontal and vertical grouting is applied on all kinds of concrete surfaces.
- It is suitable for use on interior and exterior surfaces.

Advantages

It provides waterproofing by forming a waterproof film layer on the applied area. It has high UV resistance.

Preparation of the Surface

- The surface to be covered must be clean and solid.
- All foreign substances that will counteract adhesion should be cleaned.

Application Details

- It is ready for use.



- It allows very comfortable application with roller or brush.
- It can be applied very comfortably by everyone.
- The application must be made in two layers.
- 1 hour between layers should be expected.

Thinning

- It is ready for use.
- It does not require thinning.

Application Requirements

The application must be made in two layers.

Application Tools

Roller, brush

Warnings & Suggestions

- Foreign materials must not be added.
- The product cover should not be left open.
- Avoid contact with eyes and skin.

Technical Information

Technical Information is relative to 55% (± 5 °C) relative humidity environment at 23 °C (± 2 °C).

Content	Solvent based resin
Thinning	Ready for use.
Mixture Density	0.80 - 0.85 gr/cm ³
Application	+5°C / +35°C
Temperature	30-40 minutes
Drying Time Touch	2 hours
Time Full Drying	24 hours



Consumption

En az iki kat uygulama yapılır.
Her bir kat için 200 gr/m²



Packaging

1 - 3.5 - 5 kg.
Tin Box



Shelf Life

1 year from the date of production
in drought and dry environments



Color

Transparent