



## Nouvo Pearl Paint

### Product Description

It is a water-based interior paint that is applied for decorative purposes on surfaces, it can be wiped, and it provides pearlescent patterns depending on the reflection of the light with different application apparatus, and it provides the creation of environmentally friendly, high-coverage, flexible structure.

### Advantages

Fully wipeable feature

### Surface Preparation and Application

- The surfaces to be applied must be smooth, solid, dry and free from dust.
- Ambient and surface temperature during application should be between +5 - +35°C.
- Newsan Surface Correction Paste should be used for pits and cracks that need to be filled.
- After waiting for 18 - 24 hours on Newsan Transfer Primer and painted surfaces, Newsan Matt / Semi-Matte paint is applied as a single coat with short-haired satin roller in the desired color.
- After 4 hours, Nouvo Pearl is applied as the second layer with the desired pattern.

### Application Apparatus

Satin roller, brush and Decorative Pearl Paint Printing Effect Sponge

### Application Apparatus

Application is done with roller and brush.

### Drying time (25 °C, 50% Relative Humidity)

- Completes touch drying in 2 hours and
- Hard drying in 24 hours.



### Consumption

15-20 m<sup>2</sup> / L on one layer

### Thinning

It is ready for use.

### Packaging

0,75 L - 2,5 L - 15 L

### Storage

It can be stored for 1 year in unopened packaging, in a cool place, protected from direct sunlight and frost.