



Interior Wall Export Interior Wall Water- Based Plastic Paint

Product Description

It is a styrene acrylic copolymer based, inhale matte paint with high sealing power.

Application Areas

It is used on all kinds of wall surfaces in the interior of buildings.

Advantages

- It is interior wall paint that combines economy and quality.
- It is water-based and has high inhalation ability.
- It provides perfect integration with the surface on which it is applied.
- It does not crack, swell and spill.

Application Instruction

- Before painting (paste and primer applied), the surface must be dust free, clean and dry.
- It should be thinned, mixed and homogenized according to thinning rate.
- On surfaces where color change is desired, the Newsan transfer primer can be applied as a single layer before application.
- On the surfaces whose sub-surface treatments are completed (paste and primer applied), after 24 hours, it is diluted with water by 20-25% by volume and applied at least 2 coats by brush or roller.
- In order to obtain proper application, one-way sweeping should be done, and more scanning should be avoided.
- 2-3 hours should be waited considering the seasonal differences between the coats.
- Attention should be paid not to make overlaps.



Paintable Area

Depending on the surface on two layers;

- 10-12 m² with 3,5 kg
- 28-30 m² with 10 kg
- 50-52 m² with 20 kg can be painted.

Application Apparatus

Application is done with roller and brush.

Drying Time (At 23°C (±2°C), 55% (±5°C))

- Second Layer Application: 2-3 hours
- Last Drying: 24 hours

Thinning

It is recommended to apply two coats by thinning at most 20-25%.

Packaging

20 / 10 / 3.5 kg. PE Bucket

Storage

It can be stored for 1 year in unopened packaging, in a cool place, protected from direct sunlight and frost.