



Interior Wall Silicone Water-Based Silk Gloss Paint

Product Description

It is a glossy interior paint with a styrene acrylic based, silky-looking silicone additive, high coating and cleanable.

Application Areas

It is an easy to apply high quality indoor wall paint.

Advantages

- Thanks to its silicone additive, it has a high-water repellent property and allows the removal of stains such as watercolor, pencil, ketchup on the surface.
- It allows the surfaces to breathe,
- it is odorless,
- It is human and environmentally friendly,
- Easy to apply, easy to clean,
- It has a high covering.

Application Instruction

- On new surfaces to be painted; Primer is applied on paste smoothed surfaces.
- On old painted surfaces, the surface should be cleaned from all kinds of oil, dirt, loose and blistered layers.
- After the surface correction process is done where necessary, Newsan interior primer is applied to the entire surface.
- On old synthetic painted surfaces; Newsan transformation is applied in one layer after the surface is sandpapered and sanding dust is removed from the surface.
- Newsan Transformation should be applied as a single coat before applying paint on the surfaces where color change is desired.
- 24 hours after primer application, it is thinned with water by 8-10% by volume and applied in 2 coats by brush or roller.
- In order to obtain proper application,



one-way sweeping should be done and more scanning should be avoided.

- It is recommended to wait at least 6 hours between the layers.
- The temperature of the environment and the surface to be applied during the application and for the following 24 hours should be minimum +10°C.

Paintable Area

- Depending on the surface on two layers;
- 16-18 m² with 3,5 kg
- 45-50 m² with 10 kg
- 90-100 m² with 20 kg can be painted.

Application Apparatus

Application is done with roller and brush.

Drying Time

- The waiting time between the layers is min 6 hours.
- Full drying time is min. 24 hours

Consumption

Depending on the application method and the floor, with 1 kg, 4.5-5 m² area can be painted in a single coat in one coat.

iThinning

It is recommended to apply two coats by thinning at most 8-10%.

Packaging

20 / 10 / 3.5 kg. PE Bucket

Storage

It can be stored for 1 year in unopened packaging, in a cool place, protected from direct sunlight and frost.