



Interior Wall Silicone Water-Based Matte Paint

Product Description

It is a styrene acrylic based, silicone added matte interior paint with high coating and cleanable.

Application Areas

It is an easy to apply high quality indoor wall paint.

Advantages

- It is matte and smooth.
- It covers surfaces perfectly.
- It does not swell and spill.
- It hides surface faults.

Application Instruction

- It should be applied on clean, dry and smooth surfaces where the sub-surface operations have been completed (paste and primer applied).
- 24 hours after primer application, it is thinned with water by 15-20% by volume and applied in 2 coats by brush or roller.
- In practice, roll movements should be taken into consideration in one direction.
- 2-4 hours should be waited between the application coats according to the difference between summer and winter.
- Old synthetic-based surfaces should be thoroughly sanded and sand powder removed from the surface.
- The entire surface should be smoothed with Newsan Surface Correction Paste to ensure the best matte texture.
- Old solvent-based or water-based painted surfaces to be changed and old painted and heavily soiled surfaces should be primed with Newsan Primer (Newsan Transformation Primer) and new absorbent surfaces with Newsan interior primer.



- Before application, Newsan Silicone Water-Based Matte Paint should be mixed thoroughly.

Paintable Area

- Depending on the surface on two layers;
 - 12-14 m² with 3,5 kg
 - 38-40 m² with 10 kg
 - 76-80 m² surface can be painted with 20 kg.

Application Apparatus

Application is done with roller and brush.

Drying Time

- Second Layer Application: 3 hours
- Final Dry: 24 hours

Thinning

It is recommended to apply two coats by thinning at most 15-20%.

Packaging

20 / 10 / 3.5 kg. PE bucket

Storage

It can be stored for 1 year in unopened packaging, in a cool place, protected from direct sunlight and frost.