



Silicone Interior Wall White Primer

Product Description

It is a water based, silicone primer that can be applied under all interior coating materials.

Application Areas

- It is used as an emission-based coating material primer on all kinds of porous absorbent surfaces such as concrete, plaster, gypsum paste.
- It should be used on mineral-based, highly absorbent surfaces and before applying paint for the first time.

Advantages

- It penetrates the surface perfectly.
- It reduces the consumption of finish paint by 15-20%.

Application Instruction

- The surfaces to be applied should be free from dust and dirt.
- As a Paint Primer, it can be easily applied on both newly painted surfaces and on old painted surfaces.
- By distributing homogeneously on the surfaces, it ensures that the new paint adheres perfectly to the surface.
- Old synthetic-based surfaces should be thoroughly sanded, and sand powder removed from the surface.
- The cracks on the surface should be filled with the Newsan Surface Correction Paste and the surface should be corrected.
- Newsan Silicone Interior Wall White Primer should be applied to the surface with a brush, roller or spray system after thinning with 15-20% clean water.
- At least 6 hours after Newsan Silicone Interior Wall White Primer application,



topcoat coating material application should be started.

- The temperature of the environment and the surface to be applied during the application and for the following 24 hours should be minimum +10°C.
- Extremely hot surfaces should be moistened before application.

Paintable Area

Depending on the surface on one layer;

- 23-25 m² with 3.5 kg
- 65-70 m² with 10 kg
- 130-135 m² area with 20 kg can be painted.

Application Apparatus

Application is done with roller and brush.

Application Apparatus

Application is done with roller and brush.

Drying time (20 °C, 50% Relative Humidity)

- First drying : 1-2 hours
- Paint application: 6 hours
- Full Drying : 18-24 hours

Consumption

Depending on the application method and the floor, with 1 kg, 6-7 m² area can be painted in a single coat in one coat.

Thinning

Dilute 15-20% with water.

Packaging

20 / 10 / 3.5 kg. PE bucket

Storage

It can be stored for 1 year in unopened packaging, in a cool place, protected from direct sunlight and frost.