



## Newizolan Primer (Transparent Primer)

### Product Description

It is a water based transparent primer that can be used as interior and exterior primer.

### Application Areas

- It is used on construction elements such as exposed concrete, aerated concrete, drywall, brick, gypsum paste. It can be used for isolation purposes.
- It can be used on old paints, old plaster surfaces.
- If it is used before the jacketing in old buildings, it increases the adhesion strength between the jacketing adhesive and the wall.

### Advantages

- It protects and strengthens the surface.
- It increases final coat strength.
- It allows convenient application.

### Application Instruction

- In cases where the insulation primer will be used;
- Newizolan primer thinned according to the thinning rate when it will be used as insulation material for its water-repellent feature, is applied on the painted surface or on surfaces such as plaster, exposed concrete that will not be applied with paint, by roller or brush.
- In the application made for isolation, the product should not be painted over as it will form a film on the surface. Otherwise, the surface of the paint will crack, remove and paint cannot hold. In cases to be used as a paint primer, attention should be paid not to trap during application, film should be created on the surface should be prevented. Otherwise, it causes cracking and wavy



appearance in the paint to be applied on it.

### Application Suggestion

It is recommended to wait 1 day for the application of the final coat of paint.

### Consumption

60 - 70 gr / 1m<sup>2</sup> area can be painted. (When thinned by 1/7)

### Thinning

- It is thinned with water.
- In exterior applications; 1 lt; 5 lt. water In
- interior applications ; 1 lt; 7 lt. as water
- Insulation Primer ; 1 lt; 2 lt. water.

### Paintable Area

- 45 m<sup>2</sup> with 0.75 lt.
- 100 m<sup>2</sup> with 2.5 lt.
- 450 m<sup>2</sup> with 7.5 lt.
- It can be painted in a single layer of 900 m<sup>2</sup> with 15 lt.

### Packaging

0.75 - 2.5 - 7.5 - 15 lt. PE bucket

### Storage

It can be stored for 1 year in unopened packaging, in a cool place, protected from direct sunlight and frost.