

# Exterior **Silicone Primer**

# **Product Description**

It is a water based, silicone primer that can be applied under all exterior coating materals.

# **Application Areas**

- It is used as an emission-based coating material primer on all kinds of porous absorbent surfaces such as concrete, plaster, gypsum paste.
- It should be used on mineral-based, highly absorbent surfaces and before applying paint for the first time.

## Advantages

- It penetrates perfectly into the surface, ensuring that the surface is filled evenly.
- It reduces the consumption of finish paint by 15-20%.

#### Application Instruction

- The surfaces to be applied should be free from dust and dirt.
- Surface and ambient temperature should be
- between + 5- + 30 ° C during application.
  As a Paint Primer, it can be easily applied on both newly painted surfaces and on old
- painted surfaces.
  - By distributing homogeneously on the surfaces, it ensures that the new paint
- adheres perfectly to the surface.
  Old synthetic-based surfaces should be thoroughly sanded, and sand powder
- removed from the surface.
  - Cracks in the surface should be filled and the
- surface corrected.
  - All water-related insulation measures should
- be taken on the surface to be applied.
  Application tools should be washed with water immediately after use.



#### Paintable Area

Depending on the surface on one layer;

- 23-25 m² with 3.5 kg
- 65-70 m<sup>2</sup> with 10 kg
- 130-135 m<sup>2</sup> area with 20 kg can be painted.

## **Application Apparatus**

Application is done with roller and brush.

## **Drying Time**

- First drying: 1-2 hours
- Paint application: 6 hours
- Full Drying: 18-24 hours

#### Consumption

Depending on the application method and the floor, with 1 kg, 6-7 m<sup>2</sup> area can be painted in a single coat in one coat

#### Thinning

Dilute 15-20% with water.

#### Packaging

20 / 10 / 3.5 kg. PE Bucket

#### Storage

It can be stored for 1 year in unopened packaging, in a cool place, protected from direct sunlight and frost.