



Exterior Water-Based Silicone Paint

Product Description

It is a styrene copolymer emulsion based, silicone waterproof matte topcoat exterior paint.

Application Areas

It is applied to mineral surfaces such as black plaster, concrete, cement sheet and old painted surfaces on the exterior.

Advantages

- It is water-based and has high inhalation ability.
- It has a matt and smooth appearance.
- It does not smell as it does not contain solvent and is diluted with water, it does not harm human and environmental health.
- It does not swell and spill.

Application Instruction

- The application surface should be cleaned from all kinds of oil, dirt, loose and blistered layers.
- In glassy and bright tissues, a surface should be formed where the paint will hold.
- Capillary cracks should be filled with Newsan Surface Correction Paste.
- Newsan Silicone Exterior Wall White Primer should be applied as one layer on plastered, new and solid surfaces.
- Newsan Silicone Exterior Wall White Primer should be applied on cement based decorative plaster used in the thermal insulation system.
- Newsan Silicone Exterior Wall White Primer should be applied as one layer on plastered, new and solid surfaces.
- Old synthetic-based surfaces should be thoroughly sanded, and sand powder removed from the surface.



- Application tools should be washed with water immediately after use.
- The temperature of the environment and the surface to be treated should be minimum + 10°C during the application and for the following 24 hours and the surface should not receive precipitation.

Paintable Area

- Depending on the application surface;
When Newsan Silicone Exterior Wall Water-based paint primer is used, 2 - 3 m² with 1 kg. depending on the surface on two layers,
- 4 - 6 m² of surface with when 1 kg depending on the surface on one layer when primer is used

Application Apparatus

Application is done with roller and brush

Drying Time

- First drying : 4 hours Second layer
- Application : 12 hours
- Full Drying : 24 hours

Consumption

Depending on the application method and the floor, with 1 kg, 4-6 m² area can be painted in a single coat in one coat.

Thinning

At least 24 hours after the application of the primer, it should be applied twice by thinning with water at a rate of 10-15%.

Packaging

20 / 10 / 3.5 kg. PE Bucket

Storage

It can be stored for 1 year in unopened packaging, in a cool place, protected from direct sunlight and frost.