



Exterior Water-Based Acrylic Paint

Product Description

It is a water-based acrylic copolymer based, silicone, waterproof, matte finish exterior paint.

Application Areas

- It can be used safely on concrete, gas concrete, briquette, brick, plaster and similar mineral surfaces.
- It can be applied on old painted surfaces that are in good condition.

Advantages

- It is not affected by heavy weather conditions such as rain, snow, humidity, extreme cold or hot.
- It penetrates the surface perfectly. It has a matte appearance.

Application Instruction

- The surfaces to be applied should be free from dust, dirt and oil that reduces adhesion, and should be completely cleaned from old and blistered paint layers and made dry, solid and clean.
- Old synthetic-based surfaces should be thoroughly sanded and sand powder removed from the surface.
- Newsan exterior primer is used for old painted or mineral based surfaces to be painted.
- All water-related insulation processes of the surface must have been done.
- Before application, the Newsan Water-Based Acrylic Paint should be thoroughly mixed and applied in 2 layers.
- The temperature of the environment and the surface to be treated should be minimum 10 °C during the application and for the following 24 hours and the surface should not



receive precipitation.

- Application should not be done in very hot weather, strong winds, fog, high relative humidity or weather that expects precipitation.
- Extremely hot surfaces should be moistened before application.
- Application tools should be washed with water immediately after use.

Paintable Area

- Depending on the application surface; When Newsan Exterior Wall Water-based acrylic paint is used, 2 - 3 m² with 1 kg. depending on the surface on two layers,
- 4 - 6 m² of surface with when 1 kg depending on the surface on one layer when primer is used can be painted.

Application Apparatus

Application is done with roller and brush

Drying time (20 °C, 50% Relative Humidity)

- First drying : 4 hours
- Second layer Application : 12 hours
- Full Drying : 24 hours

Consumption

Depending on the application method and the floor, with 1 kg, 4-6 m² area can be painted in a single coat in one coat.

Thinning

At least 24 hours after the application of the primer, it should be applied twice by thinning with water at a rate of 10-15%.

Packaging

20 / 10 / 3.5 kg. PE Bucket

Storage

It can be stored for 1 year in unopened packaging, in a cool place, protected from direct sunlight and frost.