



## SIL-STAR Silicone Exterior Wall Paint

### Product Description

It is a exterior wall paint water-based, high coverage, comfortable application thanks to its superior spreading power, silicone and semi-gloss appearance.

It is a water-based silicone exterior wall paint that creates a beading effect thanks to its stain-free technology and water repellent feature.

### Areas of Use

It is applied on conventional plaster, concrete, gross concrete, hardboard, gas concrete, brick and old painted surfaces.

### Advantages

- High stain resistance,
- Full Wipe ability,
- Low odor,
- High coverage.

### Preparation of the Surface

- Any dirt and dirty floors that prevent the product from sticking should be cleaned on the surface to be applied.
- The surface to be applied should be dry and clean without moisture.

### Application Instruction

- It should be applied on clean, dry and smooth surfaces tub-surface treatment is completed (Newsan Surface Correction Paste - and Newsan Silicone Exterior Wall Primer applied).
- It must be thinned according to the thinning rate written on the packaging, mixed and made homogeneous.
- First, paint is applied to the area ready for application with the help of a brush, and then, topcoat paint is applied with a suitable



roller in min 2 coats.

- In practice, roll movements should be taken into consideration in one direction.
- 2-4 hours between application coats depending on the ambient temperature should be expected.
- Care should be taken not to overlay the cross bearings.
- In order to obtain a homogeneous and more covering surface, it is recommended to perform "Scanning" process after 2-3 minutes depending on the ambient temperature, with the same roller and over the painted surface without painting the roller.

### Paintable Area

- 17.5-28 m<sup>2</sup> with 3.5 kg
- 50-80 m<sup>2</sup> with 10 kg
- 100-160 m<sup>2</sup> with 20 kg

### Thinning

It is recommended to apply two coats by thinning at most 10-15%.

### Consumption

5-8 m<sup>2</sup> area with 1 kg can be painted.

### Application Tools

With roller, brush, gun (when thinned 10%)

### Drying Time

- Waiting time between layers is min. 2 hours.
- The complete drying time is min. 24 hours.

### Packaging

20 / 10 / 3.5 kg. PE Bucket

### Storage

It can be stored for 1 year in unopened packaging, in a cool place, protected from direct sunlight and frost.