



## Exterior (Texture) Grainy Paint

### Product Description

It is an acrylic based, matte, grainy texture topcoat exterior paint with excellent covering power.

### Application Areas

It can be used safely on concrete, gas concrete, briquette, brick, plaster and similar mineral surfaces.

### Advantages

- It is resistant to moisture and water.
- It is extremely resistant to the negative effects of sunlight and salty moisture on the seacoast.
- With its ability to breathe, it allows the moisture in the wall to be exhaled.

### Application Instruction

- The surface to be applied should be cleaned from all kinds of oil, dirt, loose and blistered layers, and a surface should be formed where the paint can hold on to glassy and bright tissues.
- Capillary cracks should be filled with Newsan Surface Correction Paste.
- Newsan Silicone Exterior Wall White Primer should be applied as one layer on plastered, new and solid surfaces.
- Primer should be applied on cement based decorative plaster used in the thermal insulation system.
- Application should be made at least 24 hours after priming.
- It is applied as a single coat without thinning.
- When two layers of application are requested, the first layer is 10-15% and the second layer is applied without thinning.
- The product, which is transferred to the surface with a roll of lambskin, is patterned



with a coral roll.

- Application should be avoided in rainy and humid, extremely windy and hot weather.

### Paintable Area

- Depending on the surface in the application; Depending on the pattern thickness, 0.8-1 m<sup>2</sup> of area is painted with an average of 1 kg.
- The consumption rate in 1 m<sup>2</sup> is 1.30-1.35 kg. Consumption may vary depending on the surface and pattern.

### Application Apparatus

It is applied by roller; pattern is given by coral roller.

### Drying time (25 °C / 50% Relative Humidity)

First drying : 2-4 hours

Full Drying : 18-24 hours

### Consumption

Depending on the surface and pattern in a single layer; 15-20 m<sup>2</sup> area is painted with 20 kg

### Thinning

It is recommended to apply two (2) layers with a maximum of 5% thinning.

### Packaging

20 kg. PE Bucket

### Storage

It can be stored for 1 year in unopened packaging, in a cool place, protected from direct sunlight and frost.

**Application Requirements**

- The ambient temperature should be between +5°C and +35°C.
- Stir before application.
- Do not apply on very hot surfaces with plenty of breeze or direct sun.

**Application Tools**

Brush, Roller, Spray

**Warnings & Suggestions**

- Foreign materials must not be added.
  - The amount of consumption indicated may vary depending on the surface and application conditions.
  - It must be stored in a cool and dry environment.
  - Notch may be required to check the adherence of previously painted surfaces.
  - One day before the application of decorative coating and one-layer application should be done.
-