



Luxury Anti-Rust Paint

Definition

It is alkyd resin based, high coverage and rust preventing, lead-free, topcoat, luxury matte paint.

Areas of Use

It is applied on iron surfaces indoors and outdoors.

Advantages

- It has high covering power.
- It protects the iron surfaces against rust thanks to the pigments in its alkyd and anti-rust anticorrosive structure.
- It adheres perfectly to the surface to which it is applied.
- It does not contain lead.
- It creates a solid, smooth surface and makes the surface to be applied ready for the final layer application.

Application Instruction

- The surfaces to be applied should be cleaned from all kinds of pollution such as oil, rust.
- The surfaces to be primed for the first time should be thoroughly sanded, oil and dirt should be wiped with the base soaked in synthetic thinner, rusty surfaces should be cleaned with brush and scraper.

Specifications (20 ° C and 65% RH)

- Colors: Gray, Red, Green
- Structure: Synthetic alkyd resin based
- Thinner: Synthetic thinner
- Density: Approx. 1.60 g / cm³ (± 0.1)
- Flash Point: 36 °C

Drying Time

- Application Temperature: + 5 °C / + 35°C
- Drying Time Topcoat: 4 hours



- Application drying: 24 hours
- Touch drying: 1-2 hours
- Lower temperature and higher relative humidity prolong drying time.

Thinning

It is thinned with 5-10% synthetic brush thinner when applied with brush and roller, 10-15% synthetic sprayer.

Primable Area

Depending on the application floor with 1 kg, 10-12 m² with 1 kg in one coat. Anti-rust primer can be made.

Packaging

1 kg. / 3 kg. / 20 Kg. Tin Bucket

Storage

- It is at least 1 year in its original unopened package in a cool and dry environment.
- To safely store the remaining paint when the product remains in the package, it should be added from the thinner used until the top of the paint is completely covered or the mouth of the packaging should be tightly closed, and it should be turned 180° 1 or 2 times.

Application Tools

Brush, roll, spray gun

Cleaning of Tools

Application tools should be cleaned with synthetic thinner immediately after use.

Hazard Warnings

R 10: Flammable.

R 65: Harmful: May cause lung damage if swallowed.

S 1/2: Keep locked up and out of the reach of children.

S 13: It should be kept away from food, drink and animal feed.

S 20: Do not eat or drink while applying the product.

S 45: In case of accident or if you feel unwell, seek medical advice immediately. (Show the label to healthcare professionals.)

S 46: If swallowed, seek medical advice immediately and show this container or label.

S 53: Obtain special instructions for use before use.

S 56: Dispose of this product and its container at hazardous or special waste collection points.
