



## RM-600 Rapid Matte Paint

### Product Description

It is a solvent-based, matt-looking, fast-drying, industrial paint resistant to external weather conditions.

### Areas of Use

- On all metal surfaces
- It is used in the painting of tools such as machinery, agriculture, home, garden tools, tractor, trailer, transformer, auto-radiator parts, barrel, valve, steel cupboard, table etc

### Surface Preparation

- The application surfaces should be cleaned from all kinds of materials, dirt, rust and oil that will reduce adherence.
- If necessary, it should be primed with an industrial rapid primer

### Application Details

- It is applied in two coats directly on metal or primed surfaces.
- The second coat should be applied within 1 hour after the first coat is applied and / or after completing the chemical drying.
- Applying the second coat without completing the chemical drying causes the paint film to wrinkle.

### Thinning

It can be thinned 15-20% with industrial thinner

### Drying time (23°C 50% relative humidity)

Completes touch drying in 15-20 minutes and hard drying in 12 hours.

### Consumption

8-10 m<sup>2</sup> with 1 kg



### Application Tools

Paint gun

### Packaging

20 kg. Tin Box

### Storage

- It should be stored in closed, protected places in its original packaging, protected from direct sunlight and frost.
- Storage life is 1 year in original.

### Warnings & Suggestions

- Application tools should be cleaned with thinner immediately after work.
- + 10 °C + 35 °C during application.

### Hazard Warnings

R 10: Flammable.

R 65: Harmful: May cause lung damage if swallowed.