



## EPO-P Orange Peel Appearance Epoxy Paint

### Product Description

Thanks to its two-component, epoxy-based, solvent-based orange peel roughness, it is a coating material that does not slip.

### Application Areas

- It is applied on metal and concrete surfaces.
- In the coating of concrete marble and mosaic floors,
- In industrial floors, warehouses,
- In the coating of loading / unloading areas,
- It is applied as a rough finish in the parking lot and service areas.

### Advantages

- It is suitable for pedestrian traffic.
- It is possible to repair.
- It does not allow wear and friction.

### Ambient

- Hardener is added to the main material.
- It is mixed with a low speed mixer for 5 minutes until a homogeneous mixture is obtained.
- The prepared mixture is poured into damaged areas for repair and leveled with trowel.

### Application Apparatus

Brush, roll, airless, pistole.

### Drying Time

Hardening; 12 hours

### Consumption

0.5 - 0.6 kg. / m<sup>2</sup> in a single coat

### Thinning

It is ready for use.



### Packaging

20 Kg. (17.5 kg resin + 2.5 kg. hardener)

### Storage

It can be stored for 1 year in unopened packaging, in a cool place, protected from direct sunlight and frost.

### Warnings & Suggestions

- Application tools should be cleaned with thinner immediately after work.
- Ambient temperature should be between +10°C / +35 °C.

### Hazard Warnings

R 10: Flammable.

R 65: Harmful: May cause lung damage if swallowed.

### Note

- It is not applied on sun-exposed surfaces.
- It has no resistance to sun and UV radiation.